

# TOWN OF PAISLEY.

Platted from the field notes and original plats by R.H. Rogers Aug 25 & 27, '88

Scale 1 Inch = 100 Feet

## Dedications.

Field Notes for the Survey of the Town of Paisley. Beginning at a point 13.76 chains South and 51.61 chains West from the 1/4 Sec corner between Sec 19 and 24 Township 33 South Range 18 and 19 E at which point establish the corner of the Town of Paisley in the County of Lake and the State of Oregon from which said Town corner I proceed to survey the town as follows to wit: Beginning at an angle of N3°30'W and 53°30'E along the West line of Main Street said street being one hundred feet in width, Mill Street being at right angles with Main St and 66 feet in width. The Blocks A, B, C and D are 200 East and West 300 feet North and South, with alleys running North and South through Blocks C and D, the last named blocks containing 12 lots each, the size of each lot being 50x20 feet. Blocks A and B contain 6 lots each being 50x200 feet in size, there being no alleys in these blocks.

I certify the foregoing to be true and correct  
 (sd) J.H. EVANS, Surveyor Dec 14 1879.  
 Page 6 Old Plat Book.

The South addition to the town of Paisley consists of five lots being 100x200 feet in size divided from the original town plat by West Street which is 66 feet in width. The east addition to said town consists of Block E containing 12 lots with one alley running through said lots North and South 20 feet in width, the lots being 50x110 feet divided from the original plat by Chewaucan Street being 60 feet in width. The North addition to Paisley consists of two lots being 75x100 and lies immediately adjacent the original plat as per plat hereto attached.

acknowledgment of owner only, dated October 1st 1881.  
 Page 19 Old Plat Book.

Field Notes of the Survey of the Second addition to the Town of Paisley. Beginning at a point at the intersection of the North line of Mill Street with the East line of Chewaucan Street - which point is 300 feet North 86°30' East from the established corner of the Town of Paisley County of Lake State of Oregon. Running thence N86°30' East along the North line of Mill Street 240 feet thence N3°30'W at right angles to said Mill Street 65 feet thence S86°30'W 240 feet to the East line of the extension of Chewaucan Street thence S3°30'E along the East line of the extension of said Chewaucan Street 650 feet to the place of beginning. The above described street is as Block F and is divided into lots as shown on the annexed plat. Lots 1, 2, 3, 4 and 5 are each 40 feet front on Mill Street by 125 feet deep. Lots 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16 and 17 are each 75x100 feet. There above run through the block East and West each 25 feet in width as shown on the plat hereto annexed. Block G as shown on said plat forms a part of the aforesaid second addition and is described as follows. Beginning at a point 386 feet North 3°30' West from the aforesaid established corner to the Town of Paisley. Running thence North 3°30' West 170 feet thence North 86°30' East 100 feet to the place of beginning. Block G is not subdivided.

I certify the foregoing to be true and correct, Paisley Oregon  
 July 7 1883  
 (sd) J.L. Ramsey U.S. Dept. Surveyor.  
 Page 23 Old Plat Book.

Survey of the West, Second North and Second South Additions to the Town of Paisley Oregon. Beginning at the intersection of the North side of Mill Street which point is South 86°30' West, 240 feet from the established corner to the town of Paisley. Run thence North 3°30' West 300 feet; thence S86°30' West 150 feet; thence S3°30' East 300 feet; thence North 86°30' East to the place of beginning. The above mentioned addition is designated as Block I and is divided into lots, and bounded by streets and alleys as shown by the accompanying plat.

Field notes of the Second North Addition to the Town of Paisley Oregon. Beginning at the N.W. corner of the North Addition Run thence N3°30' West along the East side of Main Street 200 feet; thence N86°30' East at right angles to Main Street 200 feet along South side of River Street; thence South 3°30' East along West side of Chewaucan Street and at right angles to River Street 350 feet; thence S86°30' West 100 feet thence N3°30' West 150 feet thence South 86°30' West 100 feet to place of beginning. Said addition being designated as Block H and divided into lots and bounded by streets and containing alleys, as shown by the accompanying Plat.

Field notes of Survey of Second South Addition to the Town of Paisley Oregon. Beginning at the intersection of the West side of Main Street, and the South side of West Street; thence I run South 3°30' East at right angles to West Street along the West side of Main Street; thence South 3°30' East 100 feet, thence South 86°30' West 800 feet; thence North 3°30' West 300 feet; thence North 86°30' East 200 feet to the place of beginning. Said addition embracing Block I and the South Row of Lots in Block I, being the South 1/3 of Block I and divided into lots and bounded by streets and as shown by accompanying Plat.

Witness my hand this 27 day of June A.D. 1887  
 (sig) Lincoln Taylor, County Surveyor.



Note in Block G two courses are omitted. R.H.R.